

ABQ-820C COLOR QUAD SPLITTER

- ✓ 4CH real time Quad
- ✓ Anti rolling 4channel Switcher
- ✓ Full,Quad,Pip1,Pop2 display mode
- ✓ Alarm in/out
- ✓ Freeze function
- ✓ 2X Zoom function
- ✓ NTSC/PAL System
- ✓ Optional infra-red remote control
- ✓ 19" Half rack system
- ✓ High Resolution
- ✓ 720 x 480 pixel NTSC,720 x 580 pixel PAL)
- ✓ DC free voltage 12V ~ 24V



System	525 lines, 60 fields per second (NTST System), 625 lines, 50 fields per second (PAL System)
Input Signal	Composite video(1.0Vp-p 75i×U), sync. Negative
Output Signal	Composite video(1.0Vp-p 75§Û), sync. Negative
BNC connector	4 video in/out, monitor out. VCR in/out
Trigger output	relay n/o, common (3A max)
Alarm input 1,2,3,4	DC 4~5V(Open), DC 0~0.8V(Closed)/5.7k§Û
Alarm Duration	1 ~ 60 sec
Date display format	Europe/America/Asia
Time display format	HH/MM/SS, SS/MM/HH (dual mode)
DATA storage Period	About 31days
Operating temperature range	41 ~ 104°C
Operating humidity range	80% or less
Power requirements	DC12 ~ 24V Free Voltage ,1.0A
Power consumption	Approx 12W
Dimensions (inch)	8.6(W) x 1.7(H) x 9.5(D)
Weight	Approx 6.6 lbs

*Above specifications and design subject to change without notification