

CT-2.8PRO

CCTV CAMERA/CABLE TESTER



- ◆ 2.8" TFT-LCD, 960H x 240V Resolution Display
- ◆ RS-232, 485, 422 Communication
- ◆ Tests LAN UTP Cable
- ◆ Comes with a Carrying Bag
- ◆ Rechargeable

Model Name	CT-2.8PRO
Signal Mode	NTSC/PAL (Auto Adapt)
Display	2.8" Digital TFT-LCD, 960 x 240 Resolution
LCD Adjustment	Brightness, Contrast, Saturation
Video In/Out	1 BNC In/Out
Video Output Mode	1.0Vp-p
Communication	RS232, RS422 Simplex, RS485
Compatible PTZ Protocol	More Than 20 Protocols Including PELCO-D/P, Samsung, and Panasonic
Baud Rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200 BPS
Color Bar Generation	Displays Channel Colorbar Video Signal for Testing Monitor or Video Signal
UTP Cable Test	Tests Connection Status, and Displays the Result
RS485 Data Monitor	Captures and Analyzes the Command Data
Power Supply	DC 5V, 2A
Battery	Built-In 3.7V Lithium Polymer, 2000mAh
Recharge	Recharge Time: 3~4 Hr, Operates for 11 Hr/Recharge
Operating Temperature	-30~+70°C
Operating Humidity	30~90%RH
Dimensions/Weight	6.6L x 3.8W x 1.9H Inch / 0.6 LBS

*Above specifications and appearance of the product subject to change without notice