

# GN-605

## Wide Dynamic Range Camera

- ✓ Wide Dynamic Range (WDR)
- ✓ Day & Night (IR Cut Filter Removeable)
- ✓ 480 TV lines
- ✓ On Screen Display menu setting
- ✓ Privacy zone
- ✓ Dual voltage



Signal System	NTSC : 525 Lines
Scanning System	2:1 Interlace
Scanning Frequency(H)	15.734 KHz
Scanning Frequency(V)	59.94 Hz
Sync System	Internal
Image Sensor	1/3 inch Double Scan CCD
Total/Effective Pixels No.	410K/380K
Lens Mount	C/CS Mount
Iris Mode	Video/DC
S/N Ratio	More than 48dB(AGC Off)
Resolution	Horizontal : 480 TV Lines
Video Output Level	1.0 Vp-p (75 Ohms, Composite)
Min. Illumination	0.5 Lux (Color), 0.001 Lux (DSS, B/W)
WDR(Wide Dynamic Range)	Auto/On/Off
Day & Night(ICR)	Auto/Day/Night(ICR), Option
Day & Night Sensitivity	Auto / 0 (Bright) ~ 200 (Dark) Mode
Filter Delay	Auto / 0 Sec.~60 Sec. Mode
Digital Slow Shutter	Off/2FLD~20FLD/40FLD/80FLD/160FLD
Privacy Zone	On/Off(1~4 Area)
Digital Zoom	3x
Shutter Speed	1/60 ~ 1/10,000 Sec
White Balance	Auto / Hold / Manual
AGC/BLC/Flickerless	On / Off
Camera ID/Zone Label	On / Off
Mirror/Freeze/Negative	On / Off
Supplied Voltage	AC 24V (20~28V) or DC 12V (10V~15V)
Power Consumption	500mA 6.0W (max)
Dimensions (W x H x D)	2.6 x 2.3 x 5 inch
Weight	Approx. 0.9 lbs

\*Above specification and design subject to change without notification