

KPC-ZA880NH

880x Power Zoom Color CCD Camera

- ✓ High Resolution Sony 1/4" Super HAD CCD
- ✓ 480 TV Line
- ✓ Built-In 22x Optical Power Zoom Lens
- ✓ 40x Digital Zoom
- ✓ On-Screen-Display Setting
- ✓ Auto Fucus/Exposure



| | |
|---------------------------|--|
| Image Sensor | Interline 1/4" Sony Super HAD CCD |
| Total Pixels | 811H x 508V |
| Effective Pixels | 768H x 494V |
| Horizontal Resolution | More than 480 TV Lines |
| Lens | 22x Zoom Lens (f=3.9~85.8mm) F1.6(Wide)~F3.7(Tele) |
| Minimum Shooting Distance | 0.01m(Wide) / 1m(Tele) |
| Zoom | 22x Optical, 40x Digital |
| Scanning Frequency | 15.734(H), 59.944(V)KHz |
| Scanning System | 2:1 Interlace |
| Min. Illumination | 1.0 Lux / 30 IRE |
| Electronic Shutter | 1/60~1/10,000 Sec. |
| Video Focus | Auto/Manual (Near-Far) |
| OSD | On/Off (Function OSD, Sub-Key OSD, Menu OSD) |
| Camera Control | RS-232C, RS-485, Controller, A/D Key |
| Position Preset | 64 |
| Camera ID | On/Off |
| S/N Ratio | More than 48dB |
| Video Output | 1.0 Vp-p, Composite 75 Ohm |
| Protocol | Default / Pelco-D |
| Sync. System | Internal |
| Dimensions | 2.6W x 2.6H x 4.4L Inch |
| Operating Temperature | -10°C to 50°C |
| Storage Temperature | -20°C to 60°C |
| Weight | 0.8 lbs (approx) |
| Power Consumption | 230mA |
| Power Supply | DC 12V ±10% / Max 4.2W / 350mA |

*Above specification and design subject to change without notification