

MTR/LCD19

19" LCD MONITOR

- ✓ 19 Inch Viewable SXGA(1280x1024) LCD
- ✓ Brightness 280 cd/m²
- ✓ Contrast Ratio 500 : 1 (Typical)
- ✓ Response Time 8ms
- ✓ Analog Interface
- ✓ Built-in power supply
- ✓ Power Management (VESA DPMS)
- ✓ Plug-and-Play (VESA DDC2B Compatibility)
- ✓ TCO'03 Certified
- ✓ Support VESA Physical Mounting Interface



Size	19 inch
Type	A-Si TFT Active Matrix
Viewing Angle (H/V)	150/130(CR≥10)
Pixel Pitch (H/V)	0.294 mm (H x V)
Resolution	1280 x 1024
Contrast Ratio	500 : 1
Luminance	280 cd/m ²
Active Display Size (H x V)	376.32 x 301.056 mm
Display Color	16.2 Mil
Video	R.G.B Analog
Sync	H/V - Separate
Connector	15 pin D-sub
Horizontal	30kHz ~ 80 kHz
Vertical	60~75Hz
Max. Resolution (Analog)	1280 x 1024 @ 75Hz
Analog	720 x 400 @ 70 Hz, 640 x 480 @ 60/72/75 Hz, 800x600 @ 56/60/72/75 Hz, 1024 x 768 @ 60/70/75 Hz, 1280 x 1024 @ 60/75 Hz
VESA Arm	7.5 x 7.5 cm
Audio system	2W x 2ch / Earphone Jack
Stand	Tilt Stand
VESA Arm	7.5 x 7.5 cm
User Control	Brightness, Contrast, H/V-Position, Auto, phase, Color temperature selection, OSD location adjustment, Language, Reset, Exit
Power Source	100 ~ 240V AC 1.0A
Power Consumption	60W (Max.)
Safety & Regulations	FCC, CE, CB, VCCI, UL/CUL, CCC, PSE, GOST, TUV-GS, C-Tick, NOM, BSMI, EK, MIC
Unit Dimensions & Weight	16.9 x 17 x 7.8 inch, 10.8 lbs

*Above specifications and design subject to change without notification